



Norsat  
International Inc.

Innovative Communication Solutions



# BDC

## C-BAND EXT REF

### 3000X SERIES



#### TYPICAL SPECIFICATIONS


Noise figure	10 dB
L.O. stability	Phase locked to External Reference
Phase noise (SSB)	-73 dBc/Hz at 1kHz -90 dBc/Hz at 10kHz -100 dBc/Hz at 100kHz
Input VSWR	2.0 : 1
Output VSWR	2.0 : 1
Input Connector	SMA (f)

Conversion gain	40 dB
Gain stability over temperature	±2.5 dB at any constant frequency
Output P1dB	6 dBm
Power requirements	+15 to +24 V
Current drain	200 mA
Dimensions	180 (L) x 100 (W) x 70 (H) mm (7.1 x 3.9 x 2.8 in)
Weight	700 g / 24.7 oz
Temperature Range	-40°C to +60°C

#### FREQUENCY BANDS AVAILABLE


Input frequency (GHz)	3.40 to 4.20
L.O. frequency (GHz)	5.15
Output frequency (MHz)	950 to 1750

#### MECHANICAL DIAGRAM



## HOW TO ORDER

# BDC-3000XSC-10S



(517) 629-3000

vikingsatcom.com

sales@vikingsatcom.com

704 N. Clark Street Albion, MI 49224