

# FEED, KA-BAND DUAL-PORT, MOTORIZED



*Your Trusted Source for Satellite Equipment*



**FEED-2KA-MOTO**

- Motorized Receive-only 2-port Ka-band Linear Prime Focus Feed
- 24 volt Motor and Potentiometer for Fine Polarization Adjustment
- For New Antennas or Upgrading Legacy Systems

## **FEATURES**

- 100% Tested
- Full 250° of Travel
- Stainless Steel Hardware
- All Components Weather Resistant
- Field Replacement Components
- Hard Coat Anodized Aluminum Gears for wear protection
- Ideal for use with Research Concepts controllers
- Hi Torque 24VDC Motor / 5K 10 Turn Potentiometer
- Universal Mounting - Mounts to single pole, tripod and quadpod feed supports
- For use with new antennas or upgrading existing antennas in the field

## **SPECIFICATIONS**

Polarity	Dual
Polarization	Linear
Frequency Range	17 - 22 GHz
f/D Range	.335 to .425
VSWR	1.5:1 Max
Polarization Isolation	35 dB (Typ.)
Rotation	280°
Temperature Range	-40° C to +60° C
Flanges	WR42 Cover
Weight	5.0 lbs

FEED-2KA-MOTO\_REV004