

The IBUC Advantage

All IBUCs are equipped with cutting-edge intelligent technology:

- Highest quality & exacting performance guaranteed through individual unit testing over temperature
- Superior linearity for maximum useable output power
- Amplifier overdrive protection
- User-selectable AGC/ALC for optimal performance & compatibility with modem adaptive coding
- New high capacity microprocessor & extended M&C functions

ULTIMATE MANAGEMENT & CONTROL

- » Local Web Interface & NMS-Friendly SNMP «
- » 70+ User Configurable Thresholds & Alarms «
- » Upgraded Event Log with 1,000 Sensor Readings «
- » Performance Trend Analysis Tools & Statistical logs «
- » Embedded Web Pages for Universal Web Browser Access «

C-Band IBUC 2e

Low Energy Consumption Model



5W
to
20W

GaAs
Tech
Amplifier

3
Year
Warranty

Applications

When the requirement calls for a full-featured Block Upconverter that is powered by the modem, the **IBUC 2e** is an excellent fit. The **IBUC 2e** draws less power from the modem ODU power supply than the **IBUC 2** model. Auto-ranging DC input power is supplied via the IFL coaxial cable only. There is no external power connector.

Compatibility with a specific model modem is based on the ODU power supply capacity of that modem. It is also important to take into consideration voltage drop over the IFL cable.

Options

- High Stability Internal 10 MHz Reference with Auto-Detection
- Several Factory Select Bands
- Mounting Brackets
- Optional Type N or F-Type Input Connectors
- Waveguide or Type N Output
- Handheld Terminal

C-Band IBUC 2e

Frequency Range	RF (MHz)		IF (MHz)
Sense		Inverting	Non-Inverting
Band 1 Std C	5850 to 6425	950 to 1525	950 to 1525
Band 2 Palpa	6425 to 6725	975 to 1275	1125 to 1425
Band 3 INSAT	6725 to 7025	1150 to 1450	965 to 1265
Band 4 Ext C	5850 to 6650	950 to 1750	950 to 1750
Band 5 Full C	5850 to 6725	975 to 1850	950 to 1825

Input

VSWR/ Impedance	1.5:1 / 50 Ohm
Input Connector	Type N Female (50 Ohm)
Input Connector Options	Type F (75 Ohm), TNC (50 Ohm)
Input Power Detector Range	-55 to -20 dBm

Gain

Small Signal Gain (L-band to RF) with attenuator set to 10 dB

5W	68 dB min
10W	71 dB min
15W	72.8 dB min
20W	74 dB min

Attenuator Range 30 dB variable in 0.1 dB steps

Gain Flatness	Bands 1/2/3	Bands 4/5
Full Band	3 dB p-p max	4 dB p-p max
36 MHz	1 dB p-p max	1.5 dB p-p max
1 MHz	0.25 dB p-p max	0.25 dB p-p max

Gain Variation Over Temperature

Open Loop	3 dB p-p max	4 dB p-p max
With AGC	1 dB p-p max	1 dB p-p max

RF Output

Interface	CPR-137G or N(f)
VSWR	1.5:1 max
Rated Output Power	

	P _{1dB}	P _{Lin}
5W	+37 dBm min	35.5 dBm
10W	+40 dBm min	38.5 dBm
15W	+41.8 dBm min	40.3 dBm
20W	+43 dBm min	41.5 dBm

P_{Lin} is the maximum linear power as defined by MIL STD 188-164B

IMD3 (2 Carriers, 3 dB TOBO)	-27 dBc max
Level Stability with ALC	± 0.5 dB
Output Power Detector Range	Rated Power to -20 dB
Power Reading Accuracy	± 1.0 max
Spurious	
In Band	-60 dBc
Out Band	Complies with EN 301 443 & MIL STD 188-164B.
Harmonics	-50 dBc max
Output Noise Power Density	
	TX <- 84 dBm/Hz
	RX <- 145 dBm/Hz

SSB Phase Noise

External Reference	IBUC 2e
10 Hz	-115 dBc/Hz
100 Hz	-140 dBc/Hz
1 KHz	-150 dBc/Hz
10 KHz	-155 dBc/Hz
100 KHz	N/A
1 MHz	N/A

External Reference (Multiplexed on TX IFL)

Frequency & Level	10 MHz	-12 to +5 dBm
-------------------	--------	---------------

Internal Reference- Optional

Local Oscillator Frequency

Sense	Inverting	Non-Inverting
Band 1	7375 MHz	4900 MHz
Band 2	7700 MHz	5300 MHz
Band 3	8175 MHz	5760 MHz
Band 4	7600 MHz	4900 MHz
Band 5	7700 MHz	4900 MHz

IBUC Power Supply

Voltage	5W, 10W	18 to 75 VDC
	15W, 20W	48V ± 11V
		DC via coax only

Power Consumption

5W	50 W
10W	65 W
15W	100 W
20W	120 W

Monitor & Control

Ethernet (HTTP, Telnet, SNMPv2c) via RJ45 Connector

RS232/485, Handheld Terminal via MS-Type Connector

FSK multiplexed on TX IFL

Environmental

Operating Temperature	-40°C to +60°C
Relative Humidity	100% Condensing
Altitude	10,000 ft (3,000 m) ASL

Mechanical

5W, 10W	10.5 x 6 x 3.8 in. 267 x 152 x 97 mm 9.3 lbs (4.2 kgs)
15W, 20W	10.5 x 6 x 5.2 in. 267 x 152 x 132 mm 10.8 lbs (4.9 kgs)

Specifications subject to change without notice.

Updated 08/8/2019