

C-Band Satcom Waveguide Filters (3700 – 4200 MHz)



FLT-VS-370420-FT-GT-T



Your Trusted Source for Satellite Equipment

- Industry Leading Insertion Loss
- Drop in Replacement for Existing C-Band Satcom Filters
- Flat or Grooved Flange Options Available

SPECIFICATIONS	
Electrical Properties	
Passband (MHz)	3700 - 4200
Group Delay Variation	1.45 nSec Max within ± 0.5 MHz
Insertion Loss – Typical (dB)	1.1
Insertion Loss – Max (dB)	1.2
Rejection	60 dB Min below 3680 MHz 40 dB Min above 4230 MHz
Return Loss - Typical (dB) Return Loss - Max (dB)	20 dB 18 dB
Mechanical Properties	
Interface Flanges	UDR40 CPR-229 PDR40 CPR-229
Material	Aluminum 6061
Finish	Flanges: Chemical Conversion Waveguide: Silver Plate Exterior: Paint
Dimensions	6.75" x 2.75" x 3.87"
Weight	2.2 lbs (998 gm)
Environmental	
Operating Temperature	-40°C to +50°C

FLT-VS-370420-FT-GT-T_REV-003

Specifications are subject to change without notice

sales@vikingsatcom.com • www.vikingsatcom.com

T: 517.629.3000 • 704 North Clark Street • Albion, MI