



Storm Case

- · Five Press & Pull Latches
- · Three Double-layered, Soft-grip Handles
- Two Padlockable Hasps
- . In-line Wheels
- . Telescoping Handle
- Vortex® Valve
- Flush Powerful Hinges
- . Lightweight Strong HPX® Resin
- Watertight
- Guaranteed For Life

Storm Case Configurations

Cat. #	Description
iM2950	iM2950 Pelican Storm Case
iM2950-X0000	iM2950 Storm Case (No foam)
iM2950-X0002	iM2950 Storm Case with Padded Dividers







Storm Case Specifications

Otoriii Gasc Opecinications		
Exterior Dimensions (L x W x D)	Interior Dimensions (L x W x D)
31.30" x 20.40" x 12.20" (79.5 x 51.8 x 31 cm)	29.00" x 18.00" x 10.50" (73.6 x 45.7 x 26.7 cm)	
Lid Depth	Bottom Depth	Total Depth
2.00" (5.1 cm)	8.50" (21.6 cm)	10.50" (26.7 cm)
Weight with foam	Weight without foam	Buoyancy Max.
28.7 lbs. (13.02 kg)	20.8 lbs. (9.43 kg)	260.65 lbs. (118.23 kg)
Range Temperature	No. of Wheels	Retractable Handle
-20 / 140° F (-29 / 60° C)	2	YES

Storm Case Certificates

• MIL-STD-810F • FED-STD-101C • ATA 300

Storm Case Accessories

Ctoriii Cubo Accessories		
Cat. #	Description	
iM-LIDSTAY	Lid Stay	
iM-VALVE-M-B	Manual Purge Valve	
iM2950-DIV	Padded Dividers	
iM2950-FOAM	Replacement Foam	
iM29XX-BEZEL	Base Bezel Kit	
iM29XX-BEZEL-LID	Lid Bezel Kit	
iM29XX-UTILITYORG	Utility Organizer	